

Rotary Switches

10 x 10 mm Rotary DIP Switches with 3:3 Pinout

RD1 Series

RD1H THT Top Adjust Type Terminals

RD1HF16 Flat Rotor, 16 Positions

RD1HS16 Shaft Rotor, 16 Positions

RD1R1 THT Right Angle Rows Spacing 2.54 mm

RD1R1F16 Flat Rotor, 16 Positions

RD1R1S16 Shaft Rotor, 16 Positions

RD1R2 THT Right Angle Rows Spacing 5.08 mm

RD1R2F16 Flat Rotor, 16 Positions

RD1R2S16 Shaft Rotor, 16 Positions

RD1S SMT with Top Tape Sealed

RD1SF16 Flat Rotor, 16 Positions

KRD Shaft Cover

Code

Pin No.	Position															
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
1	○	●	○	●	○	●	○	●	○	●	○	●	○	●	○	●
2	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
4	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
8	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

● Real Code (Rotor Color: White)
○ Complementary Code (Rotor Color: Red)

How to order:

RD1 + KRD

Optional: Shaft Cover

1 TYPE OF TERMINALS:

- H** THT Top Adjust Type
- R1** THT Right Angle Side Adjust Type with Rows Spacing 2.54 mm
- R2** THT Right Angle Side Adjust Type with Rows Spacing 5.08 mm
- S** SMT with Top Tape Sealed

2 ROTOR TYPE:

- F** Flat Rotor
- S** Shaft Rotor (RD1H & RD1R Only)

3 NO. OF POSITIONS:

- 08** 8 Positions
- 10** 10 Positions
- 16** 16 Positions

4 CODE:

- R** Real Code
- S** Complementary Code

5 PACKAGING TYPE:

- TB** Tube
- TR** Tape & Reel (RD1S Only)

6 (OPTIONAL): SHAFT COVER COLOR:

- B** White
- C** Red

General Specifications:

FEATURES

- » Molded-in terminals and fully sealed construction
- » Gold plated contact to ensure low contact resistance

MECHANICAL

- » Mechanical Life: 2,000 steps per position
- » Operating Force: 500 gf max.
- » Operation Temperature: -20°C to +70°C
- » Storage Temperature: -40°C to +85°C

ELECTRICAL

- » Contact Rating: 25mA, 24VDC

SOLDERING PROCESSES

- » Solderability for T.H.T.: After flux 230±5°C for 5±0.5 seconds, 95% coverage
- » Resistance to soldering heat for T.H.T.: 260±5°C for 5±1 seconds
- » Reflow soldering heat for S.M.T. (reference only): 210°C for 20 seconds or less, peak temperature 230°C or less