





Rocker Switches

21 x 15 mm SP illuminated Rocker Switches





RK3 Series

Rocker Switches
















RK3S1 ON-OFF Switching

RK3S2 ON-ON Switching



RK3S3 Indicator Light

TERMINAL	ACTUATOR	ACTUATOR MARKING	PANEL SIZE												
 <p>P 4.8mm TAB, 0.8mm THICK, Ø1.6mm</p>	<p>4 Curve (No Illuminated)</p> 	<p>A  (No Marking)</p> <p>B  OFF ON</p> <p>C  O I</p>	<p>PANEL CUT-OUT Snap-in mounting</p>  <table border="1" data-bbox="1023 1205 1481 1344"> <thead> <tr> <th>X (Panel thickness)</th> <th>Dimension Y</th> <th>Dimension Z</th> </tr> </thead> <tbody> <tr> <td>0.75 to 1.25 mm</td> <td>19.20 +0.1/-0 mm</td> <td>12.90 +0.15/-0 mm</td> </tr> <tr> <td>1.25 to 2 mm</td> <td>19.40 +0.1/-0 mm</td> <td>12.90 +0.15/-0 mm</td> </tr> <tr> <td>2 to 3 mm</td> <td>19.80 +0.1/-0 mm</td> <td>12.90 +0.15/-0 mm</td> </tr> </tbody> </table>	X (Panel thickness)	Dimension Y	Dimension Z	0.75 to 1.25 mm	19.20 +0.1/-0 mm	12.90 +0.15/-0 mm	1.25 to 2 mm	19.40 +0.1/-0 mm	12.90 +0.15/-0 mm	2 to 3 mm	19.80 +0.1/-0 mm	12.90 +0.15/-0 mm
X (Panel thickness)	Dimension Y	Dimension Z													
0.75 to 1.25 mm	19.20 +0.1/-0 mm	12.90 +0.15/-0 mm													
1.25 to 2 mm	19.40 +0.1/-0 mm	12.90 +0.15/-0 mm													
2 to 3 mm	19.80 +0.1/-0 mm	12.90 +0.15/-0 mm													
 <p>Q 4.8mm TAB, 0.8mm THICK, Ø1.4mm</p>	<p>5 Curve (Illuminated)</p> 	<p>D  O -</p> <p>E  .</p> <p>F  O II</p>													
 <p>L 2.9mm TAB, 0.8mm THICK</p>	<p>6 Flat</p> 														

How to order:

RK3

- 1** **POLES:**
- S** Single Pole
- 2** **SWITCHING:**
- 1** ON - OFF
- 2** ON - ON
- 3** Indicator Light
- 5** **TERMINAL (See above drawings):**
- P** 4.8mm TAB, 0.8mm Thick, Ø1.6mm (RK3S3 Only)
- Q** 4.8mm TAB, 0.8mm Thick, Ø1.4mm (RK3S1 & RK3S2 Only)
- L** 2.9mm TAB, 0.8mm THICK (RK3S1 & RK3S2 Only)
- 4** **ACTUATOR (See above drawings):**
- 4** Curve (No Illuminated) (RK3S1 & RK3S2 Only)
- 5** Curve (Illuminated) (RK3S1 & RK3S2 Only)
- 6** Flat (RK3S3 Only)
- 5** **ACTUATOR MARKING:**
- A** See above drawings
- B** See above drawings
- C** See above drawings
- D** See above drawings
- E** See above drawings
- F** See above drawings
- 6** **ILLUMINATION:**
- N** No Illuminated
- F** Green
- C** Red
- G** Blue (RK3S3 Only)
- D** Orange
- 7** **BASE COLOR:**
- A** Black
- H** Grey
- B** White
- 8** **ACTUATOR COLOR:**
- A** Black
- H** Grey
- B** White
- C** Red
- 9** **WATERPROOF COVER:**
- N** None Cover (Standard)
- W** With Waterproof Cover

General Specifications:

FEATURES

Single pole Rocker switch up to 20A 125VAC

MATERIALS

Contact Arm: Silver cadmium alloy
Terminal: Silver plated copper
Spring: Piano wire

MECHANICAL

Temperature Range: -20°C to +125°C

ELECTRICAL

Electrical Life: 10,000 cycles
Rating: 20A125VAC, 12A250VAC
10A125VAC, 6A250VAC
6A125VAC, 3A250VAC
6A250VAC
10(4)A250VAC~T125
Initial Contact Resistance: 20mΩ max.
Insulation Resistance: 100MΩ min. at 500VDC

All specifications are restricted to OA test criteria.
DRW: D.L. JIN, CHK: D.F. LEE, APP: H.Z. QIU